

Profiled Fillers Metallocene Polyolefin

Product Description

Premier profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapour ingress.

Product Features

Premier fillers are supplied:

- made-to-measure
- with extended base
- ventilated
- in spacer and strip form
- self adhesive
- angle-cut
- in a range of materials, thicknesses and colours

Typical Applications

- sealing eaves and ridge
- sealing hips and valleys
- sealing roof lights

Technical Information

Code	M25	M30
Type	High Tensile	High Tensile
Material	Fully closed cell metallocene catalysed polyolefins	Fully closed cell metallocene catalysed polyolefins
Colour	Black or White	Black or White
Thickness	25mm	30mm
Density (kg/m ³)	33	33
Service Temp (°C)	-70 to +100	-70 to +100
Water absorption	0.5% 28 days	0.5% 28 days
Durability (dependent upon conditions)	25 years +	25 years +

Please note: the above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 1999

Premier Sealant Systems Limited

Mercia Way Foxhills Industrial Park Scunthorpe N. Lincs. DN15 8RE England
Tel : 01724 864100 Fax : 01724 860116 Email : sales@premseal.co.uk