

Mak Dublin:
Tel: 01-4519900 / Fax: 01-4519004
E-Mail: sales@makfasteners.com

Mak Cork:
Tel: 021-4342890 / Fax: 021-4342396
E-Mail: corksales@makfasteners.com

Mak (NI):
Tel: 028-86758574 / Fax: 028-86758578
E-Mail: salesni@makfasteners.com



**MAK
FASTENER
SPECIALISTS
LTD**

Fasteners for Roofing, Cladding
and General Construction

Product Group 12 *PVC / EPDM Tape*

Description

Expanded PVC in a range of densities, they are essentially closed cell structures coated with a strong pressure-sensitive acrylic adhesive and require 30% compression to create a water seal



Typical Applications


Applications include sealing of:

- Roofing & cladding seals
- Profiled sheeting
- All types of glazing systems
- Sealing partition walls
- Heating & ventilation seal
- Vehicle bodywork
- Cold bridging in roofing & cladding
- Access doors
- Gutter joints
- Coldroom panels
- Prefabricated tanks
- Building panels
- Rooflights
- Greenhouses

Mak Dublin:
 Tel: 01-4519900 / Fax: 01-4519004
 E-Mail: sales@makfasteners.com

Mak Cork:
 Tel: 021-4342890 / Fax: 021-4342396
 E-Mail: corksales@makfasteners.com

Mak (NI):
 Tel: 028-86758574 / Fax: 028-86758578
 E-Mail: salesni@makfasteners.com



MAK
FASTENER
SPECIALISTS
LTD

Fasteners for Roofing, Cladding
 and General Construction

Product Group 12

PVC / EPDM Tape

Technical Information

	20 Series	25 Series	50 Series*
Adhesive	Acrylic		
Colours	Black/White	Black/Grey	Black/Grey
Density (kg/m ³)	100	150	200
Shore Hardness (00 Scale)	20	35	50
Tensile strength (kPa)	240	240	640
Elongation	>100%	>100%	>120%
Service temperature	-30°C - +70°C		
Application temperature	+10°C - +45°C		
UV Resistance	Excellent		
Fungi resistance	Excellent		
Oxidation resistance	Excellent		
Weather resistance	Excellent		
Shelf life	1 Year		

- SBV50 also available with a fixed Mylar liner (SBV50M)
- Premier PVC foams meet the following surface spread of flame requirements FMVSS302, DIN4102 Class B2.

Mak Dublin:
 Tel: 01-4519900 / Fax: 01-4519004
 E-Mail: sales@makfasteners.com

Mak Cork:
 Tel: 021-4342890 / Fax: 021-4342396
 E-Mail: corksales@makfasteners.com

Mak (NI):
 Tel: 028-86758574 / Fax: 028-86758578
 E-Mail: salesni@makfasteners.com



**MAK
 FASTENER
 SPECIALISTS
 LTD**

Fasteners for Roofing, Cladding
 and General Construction


Product Group 12 *PVC / EPDM Tape*

Description

PVC Barrier Tape

PREMIER

Adhesive Systems Ltd
 Sealant Systems Ltd

Features	Product Image								
<p>Product Description</p> <p>Premier PVC barrier tape is a flame retardant self-extinguishing electrical insulation tape, offering good conformability</p> <p>Typical Applications</p> <ul style="list-style-type: none"> “ Creating a thermal barrier “ Prevention of electrolytic corrosion “ Wire and cable insulation “ Colour coding of electrical cables “ Loom harnessing “ Drum or tube sealing <p style="text-align: center;"><u>Sizes</u></p> <table border="0"> <thead> <tr> <th><u>Code</u></th> <th><u>Description</u></th> </tr> </thead> <tbody> <tr> <td>12-PVCBT050</td> <td>50mmx33mtr PVC Barrier Tape</td> </tr> <tr> <td>12-PVCBT075</td> <td>75mmx33mtr PVC Barrier Tape</td> </tr> <tr> <td>12-PVCBT100</td> <td>100mmx33mtr PVC Barrier Tape</td> </tr> </tbody> </table>	<u>Code</u>	<u>Description</u>	12-PVCBT050	50mmx33mtr PVC Barrier Tape	12-PVCBT075	75mmx33mtr PVC Barrier Tape	12-PVCBT100	100mmx33mtr PVC Barrier Tape	
<u>Code</u>	<u>Description</u>								
12-PVCBT050	50mmx33mtr PVC Barrier Tape								
12-PVCBT075	75mmx33mtr PVC Barrier Tape								
12-PVCBT100	100mmx33mtr PVC Barrier Tape								