



GuardDog[®]

EXTERIOR WOOD SCREW

The New Exterior Wood Screw. Now with PoziSquare™ Drive.

Fully tested, fully guaranteed in ACQ, Cedar, Redwood and Copper Azole.

- Versatile head style can be used with the PoziSquare Drive, #2 square drive and Phillips drive.
- Guaranteed corrosion resistance.
- Color matched to blend in with pressure treated decking.
- Sharp threads quickly penetrate lumber.
- Free PoziSquare bit included.

Photograph should not be used as a reference for fastening patterns.



For more information or free samples, call FastenMaster at 800-518-3569.

GuardDog®

EXTERIOR WOOD SCREW

INSTALLATION PROCEDURE

Use a 0-1800 RPM variable speed drill (at least 14.4V if cordless). Use the PoziSquare driver bits provided. Install fastener perpendicular to deck, increasing drill speed as the screw threads into the deck. Slightly countersink. Do not overdrive. If cam-out occurs, remove and replace screw.

No Predrilling:

GuardDog's sharp piercing point allows for installation without predrilling for most applications. Predrilling is recommended at all seam joints, when fastening within 1½" of end of board, and when using hardwoods.

GuardDog PoziSquare Drive: Versatility on the job.

The patented PoziSquare Bit is engineered to work with:

- The PoziSquare Drive (Recommended drive system—Free bit enclosed)
- #2 Square Drive
- #2 Phillips Drive

This versatile drive system allows for flexibility at the jobsite. The PoziSquare drive virtually eliminates cam out during installation. (If cam out does occur during installation, the fastener should be removed and replaced with a new GuardDog screw.)

GuardDog Coating: Fully Tested, Fully Guaranteed.

The GuardDog coating has been tested and approved for use in ACQ, Copper Azole PT, Cedar, and Redwood applications. This fastener is guaranteed to protect against rust for the life of the project.

Note: Corrosion guarantee does not apply when the fastener is used within 1,000 ft. of a saltwater application.

Photograph showing GuardDog usage should not be used as a reference for fastening patterns.


PRODUCT FEATURES

VERSATILE
POZISQUARE
DRIVE

GUARANTEED
CORROSION
RESISTANT
COATING

AGGRESSIVE THREAD
DESIGN FOR
INCREASED HOLDING
POWER

SHARP PIERCING POINT
FOR FAST INSTALLATION



Part Number	Screw Length	Qty. per Box	Sq. Ft. of Deck*
FMGD158-75	1 5/8"	75	20
FMGD158-350	1 5/8"	350	100
FMGD158-1750	1 5/8"	1750	500
FMGD002-75	2"	75	20
FMGD002-350	2"	350	100
FMGD002-1750	2"	1750	500
FMGD212-75	2 1/2"	75	20
FMGD212-350	2 1/2"	350	100
FMGD212-1750	2 1/2"	1750	500
FMGD003-75	3"	75	20
FMGD003-350	3"	350	100
FMGD003-1750	3"	1750	500
FMGD312-75	3 1/2"	75	20
FMGD312-350	3 1/2"	350	100
FMGD312-1350	3 1/2"	1350	350

*Based on a fastening pattern of 2 screws per joist, spaced every 16", into standard 6" wide decking

FM08004-10M-AML